



*SEE BULLETIN BK4618 FOR OPERATING, INSTALLATION AND PARTS INSTRUCTIONS

MODEL	MODEL WITH MANUAL RELEASE	TORQUE LB.FT.	No. OF ROTATING FRICTION DISCS	MAX. RPM	THERMAL CAPACITY HPS/MIN.	INERTIA WK ² LB.FT ²	WT. LBS. PKG'D	MAGNET AIR GAP ±.005		BRACKET MATERIAL	COVER MATERIAL
								MAX.	ORIGINAL SETTING		
2-51001-05A	2-51001-050	1.5	1	3600	4	.0023	7	.150	.065	STEEL	STAMPED STEEL
2-51003-05A	2-51003-050	3	1	3600	4	.0023	7			STEEL	STAMPED STEEL
2-51006-05A	2-51006-050	6	1	3600	4	.0023	7			STEEL	STAMPED STEEL

THIS MATERIAL IS PROPERTY OF DISCO COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE FURNISHING OF SERVICES AND SUPPLIES TO THE DISCO COMPANY.

DISCO BRAKE OUTLINE DRAWING

50 SERIES, NEMA 2 (S6005, S5006)

TOLERANCE UNLESS OTHERWISE NOTED
 .001 & .002 FRACTIONS & ANGLES & 17'
 .005 & .010 DECIMALS & 17'

DESIGNED BY: [Signature]
 DRAWN BY: [Signature]
 CHECKED BY: [Signature]
 DATE: 7-9-88
 FULL

DISCO DYNAMICS
 1000 WEST BIRCHFIELD AVENUE
 DENVER, COLORADO 80202

B	2260	8-20-08	JEV	UPDATED DRAWING
A	1788	7-17-88	RM	ADDED MAGNET AIR GAP TO TABLE
REV	CHG	DATE	BY	REVISION

CAD FILE: L050024

DRAWING NO. L050024

REV. NO. B