



*SEE BULLETIN BK4655 FOR OPERATING, INSTALLATION AND PARTS INSTRUCTIONS

MODEL NUMBER	NUMBER OF ROTATING DISCS	TORQUE LB.FT.	THERMAL CAPACITY HPS./MIN.	INERTIA OF ROTATING PARTS LB.FT. ²	MAGNET AIR GAP		DIMENSIONS					COVER MATERIAL	BRACKET MATERIAL
					ORIGINAL SETTING	MAXIMUM	X	G	AC	C	N		
2-61001-524	1	1.5	6	.006	.045/.050	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
2-61003-524	1	3	6	.006	.045/.050	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
2-61006-524	1	6	6	.006	.045/.050	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
2-62006-524	2	6	6	.010	.050/.055	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
2-62010-524	2	10	6	.010	.050/.055	.100	.88	1.19	.59	4.13	1.13	STAMPED STEEL	ALUMINUM
2-63010-524	3	10	6	.015	.060/.065	.100	1.19	1.56	.96	4.50	1.44	STAMPED STEEL	ALUMINUM
2-63015-524	3	15	6	.015	.060/.065	.100	1.19	1.56	.96	4.50	1.44	STAMPED STEEL	ALUMINUM
2-63020-524	3	20	6	.015	.060/.065	.100	1.19	1.56	.96	4.50	1.44	STAMPED STEEL	ALUMINUM
2-64025-524	4	25	6	.020	.060/.065	.100	1.34	2.25	1.56	5.19	2.00	STAMPED STEEL	CAST IRON

THIS MATERIAL IS PROPERTY OF DUNLOP COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE FURNISHING OF SERVICES AND SUPPLIES TO THE DUNLOP COMPANY.

THIS OUTLINE DRAWING FOR 60 SERIES ENDMOUNT BRAKE NEMA 2 ENCLOSURE (S6524)

TOLERANCE UNLESS OTHERWISE NOTED
 .001 & .002 FRACTIONS & .001
 .001 & .002 UNLESS NOTED

DATE BY DATE BY
 1-10-83 FULL

REV CHG DATE BY REVISION

CAD FILE: L0602802

DUNLOP DYNAMICS
 1000 W. BELLEVILLE BLVD.
 BELLVILLE, OHIO 44705
 (614) 881-1000

C 2226 6-10-06 JEB UPDATED DRAWING
 B 1988 7-3-00 BSH ADDED SPRING LENGTH & 2 MODEL #S
 A 1788 7/17/98 RM ADDED AIR GAP TO TABLE
 REV CHG DATE BY REVISION

L060280 2 of 3