



*SEE BULLETIN BK4661 FOR OPERATING, INSTALLATION AND PARTS INSTRUCTIONS

MODEL NUMBER		NUMBER OF ROTATING DISCS	TORQUE LB.FT.	THERMAL CAPACITY HPS/MIN.	INERTIA OF ROTATING PARTS LB.FT. ²	MAGNET AIR GAP		DIMENSIONS*					BRACKET MATERIAL	COVER MATERIAL
WITHOUT HUB SEAL	WITH HUB SEAL "TEFC" MOUNTING					ORIGINAL SETTING	MAXIMUM	C*	AC*	G*	X	N*± 1/32		
6-61001-5141	6-61001-5140	1	1.5	6	.006	.045/.050	.100	4.81	.94	1.63	.88	1.59	316 STAINLESS STEEL	316 STAINLESS STEEL
6-61003-5141	6-61003-5140	1	3	6	.006	.045/.050	.100	4.81	.94	1.63	.88	1.59	316 STAINLESS STEEL	316 STAINLESS STEEL
6-62006-5141	6-62006-5140	2	6	6	.011	.050/.055	.100	4.81	.94	1.63	.88	1.59	316 STAINLESS STEEL	316 STAINLESS STEEL
6-62010-5141	6-62010-5140	2	10	6	.011	.050/.055	.100	4.81	.94	1.63	.88	1.59	316 STAINLESS STEEL	316 STAINLESS STEEL
6-63015-5141	6-63015-5140	3	15	6	.017	.060/.065	.100	5.13	1.25	1.94	1.19	1.90	316 STAINLESS STEEL	316 STAINLESS STEEL
6-63020-5141	6-63020-5140	3	20	6	.017	.060/.065	.100	5.13	1.25	1.94	1.19	1.90	316 STAINLESS STEEL	316 STAINLESS STEEL
6-64025-5141	6-64025-5140	4	25	6	.022	.060/.065	.100	5.44	1.56	2.25	1.34	2.05	316 STAINLESS STEEL	316 STAINLESS STEEL

*NOTE: WHEN APPLICABLE, TABLE DIMENSIONS ARE REFERENCED FROM THE BRAKE MOUNTING FACE AND DO NOT INCLUDE THE GASKET THICKNESS.