



NOTE #1:
 THE MAXIMUM SHAFT DIAMETER FOR THIS BRAKE IS 1-5/8". FOR ANY GIVEN SHAFT UP TO AND INCLUDING THIS DIAMETER, STANDARD NEMA SHAFT LENGTHS MAY HAVE TO BE SHORTENED.
 * CONSULT FACTORY FOR SPECIFIC DETAILS.

ENCLOSED HOUSING MODEL	ENCLOSED HOUSING MODEL W/HUB SEAL	TORQUE LB.FT.	No. OF ROTATING FRICTION DISCS	MAX. RPM	THERMAL CAPACITY HPS/MIN.	INERTIA WK ² LB.FT ²	DIMENSIONS										ENCLOSURE MATERIAL
							"C"	"D" ±.005		"H"	"N" ±1/32	"X"		"AC"			
								MAX.	ORIGINAL SETTING			MODEL -58	MODEL -57				
6-71010-58	6-71010-57	10	1	3600	10	.036	5.75	.060	.035	1.31	1.50	1.00	1.31	1.47	CAST IRON		
6-71015-58	6-71015-57	15	1	3600	10	.036	5.75	.060	.035	1.31	1.50	1.00	1.31	1.47	CAST IRON		
6-72025-58	6-72025-57	25	2	3600	11	.059	6.37	.060	.035	1.31	2.00	1.50	1.81	2.09	CAST IRON		
6-72035-58	6-72035-57	35	2	3600	11	.059	6.37	.065	.040	1.22	2.00	1.50	1.81	2.09	CAST IRON		
6-73050-58	6-73050-57	50	3	3600	12	.083	7.00	.065	.040	1.25	2.50	2.00	2.31	2.72	CAST IRON		
6-74075-58	6-74075-57	75	4	3600	13	.107	7.62	.065	.040	1.20	3.00	2.50	2.81	3.34	CAST IRON		

SYMBOL KEY:

- "C" = ENCLOSURE LENGTH
- "D" = MAGNET AIR GAP
- "H" = INSTALLED SPRING LENGTH
- "N" = HUB LOCATION DIMENSION
- "X" = OVERALL HUB LENGTH
- "AC" = EXTERNAL WIRING OUTLET DIMENSION

****SEE BULLETIN BK4713 FOR OPERATING, INSTALLATION AND PARTS INSTRUCTIONS**

THIS MATERIAL IS PROPERTY OF DORR COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE FURNISHING OF SERVICES AND SUPPLIES TO THE DORR COMPANY.

OUTLINE DRAWING, 70 SERIES BRAKE NEMA 4, 4 POST (S7057), (S7058)

TOLERANCE UNLESS OTHERWISE NOTED
 .005 & .010 FRACTIONS & .005
 .005 & .010

DORR DYNAMICS
MEMBER OF THE DORR GROUP

REV CHG# DATE BY REVISION

C 2240 8-11-08 BMR UPDATED DRAWING, SEE CHANGE NOTE
 B2 2030 2-28-01 BH CHANGED TO SHOW MACH. BRACKET
 B1 2030 2-28-01 BH ADDED PHL -057, COIL SPRING HEIGHT
 A 1927 5-8-00 BH 1.81 WAS 1.51

DATE 7-13-08
 DWG FULL
 DORR FILE: L070354

L070354