



MODEL NUMBER	TORQUE LB.FT.	No. OF ROTATING FRICTION DISCS	MAX. RPM	DIMENSIONS							
				C	D ±.005		H	N	X	AC	
					MAX.	ORIGINAL SETTING					
2-91025-40	25	1	2400	7.28	.065	.035	1.31	2.75	1.00	2.72	
2-91035-40	35	1	2400	7.28	.065	.035	1.31	2.75	1.00	2.72	
2-92050-40	50	2	2400	7.91	.065	.035	1.31	3.25	1.50	3.34	
2-92070-40	70	2	2400	7.91	.065	.035	1.31	3.25	1.50	3.34	
2-93075-40	75	3	2400	8.53	.070	.040	1.31	3.75	2.00	3.87	
2-93105-40	105	3	2400	8.53	.070	.040	1.31	3.75	2.00	3.87	
2-94125-40	125	4	2400	9.16	.080	.050	1.43	4.25	2.50	4.60	
2-95175-40	175	5	2400	9.78	.080	.050	1.31	4.87	3.12	5.22	

H = INSTALLED SPRING LENGTH

D = MAGNET AIR GAP

THIS MATERIAL IS PROPERTY OF IDMS COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE FURNISHING OF SERVICES AND SUPPLIES TO THE IDMS COMPANY.

FILE OUTLINE DWG. S8040 NEMA 2 END MOUNT (S8028 WITH ADAPTOR)

TOLERANCE UNLESS OTHERWISE NOTED:
 .005 ± .005 FRACTIONS ± .005
 .01 ± .012 ANGLES ± 1°

DESIGNED BY: IDMS DYNAMICS
 CHECKED BY: IDMS DYNAMICS
 DATE: 06/07/08 SCALE: 1/2"=1"
 DRAWING NO.: L090152 SHEET: 1 OF 1
 CAD FILE: L090152