



MODEL NUMBER	TORQUE LB.FT.	No. OF ROTATING FRICTION DISCS	MAX. RPM	DIMENSIONS						
				C	D ±.005		H	N ±1/32	X	AC
					MAX.	ORIGINAL SETTING				
2-91025-40	25	1	2400	7.28	.065	.035	1.31	2.75	1.00	2.72
2-91035-40	35	1	2400	7.28	.065	.035	1.31	2.75	1.00	2.72
2-92050-40	50	2	2400	7.91	.065	.035	1.31	3.25	1.50	3.34
2-92070-40	70	2	2400	7.91	.065	.035	1.31	3.25	1.50	3.34
2-93075-40	75	3	2400	8.53	.070	.040	1.31	3.75	2.00	3.87
2-93105-40	105	3	2400	8.53	.070	.040	1.31	3.75	2.00	3.87
2-94125-40	125	4	2400	9.16	.080	.050	1.43	4.25	2.50	4.60
2-95175-40	175	5	2400	9.78	.080	.050	1.31	4.87	3.12	5.22

H = INSTALLED SPRING LENGTH

D = MAGNET AIR GAP

THIS MATERIAL IS PROPERTY OF EMGS COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE FURNISHING OF SERVICES AND SUPPLIES TO THE EMGS COMPANY.

FILE OUTLINE DWG. S9040 NEMA 2 END MOUNT (S8028 WITH ADAPTOR)

TOLERANCE UNLESS OTHERWISE NOTED:  
 .005 ± .005 FRACTIONS ± .005  
 .01 ± .012 ANGLES ± 1°

DESIGNED BY: ID Dynamics  
 DRAWN BY: ID Dynamics  
 DATE: 06/07/08  
 SCALE: 1/2"=1"

4740 WEST ELECTRIC AVE.  
 MILWAUKEE, WISCONSIN 53219 U.S.A.

ISSUED BY: ID Dynamics  
 DATE: 06/07/08  
 SCALE: 1/2"=1"

DWG. NO. L090152  
 SHEET 1 OF 1  
 CAD FILE: L090152