



MODEL NUMBER	TORQUE LB.FT.	No. OF ROTATING FRICTION DISCS	DIMENSIONS						
			C	D ±.005 MAX.	ORIGINAL SETTING	H	N ±1/32	X	AC
4-91025-41	25	1	1.28	.085	.035	1.31	2.75	1.31	2.72
4-91035-41	35	1	7.28	.085	.035	1.31	2.75	1.31	2.72
4-92050-41	50	2	7.91	.085	.035	1.31	3.25	1.81	3.34
4-92070-41	70	2	7.91	.085	.035	1.31	3.25	1.81	3.34
4-93075-41	75	3	8.53	.070	.040	1.31	3.75	2.31	3.97
4-93105-41	105	3	8.53	.070	.040	1.31	3.75	2.31	3.97
4-94125-41	125	4	9.16	.080	.050	1.43	4.25	2.81	4.60
4-95175-41	175	5	9.78	.080	.050	1.31	4.87	3.44	5.22

H = INSTALLED SPRING LENGTH  
 D = MAGNET AIR GAP

THIS MATERIAL IS PROPERTY OF IDDS COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE PURSUIT OF SERVICES AND SUPPLIES TO THE IDDS COMPANY.

FILE OUTLINE DWG. S9041 NEMA 4 END MOUNT (S8029 WITH ADAPTOR) WITH HUB SEAL

TOLERANCE UNLESS OTHERWISE NOTED:  
 DIM ±.010 FRACTIONS ±.010  
 DIM ±.010 HOLE ±.010

DESIGNED BY: IDDS DYNAMICS  
 DRAWN BY: IDDS  
 DATE: 06/07/08 SCALE: 1/2"=1"

ISSUED BY: IDDS  
 DATE: 06/07/08 SCALE: 1/2"=1"

DWG. NO. L090153 SHEET NO. 1 OF 1