



MODEL NUMBER	TORQUE LB.FT.	No. OF ROTATING FRICTION DISCS	DIMENSIONS						
			C	D ±.005 MAX.	ORIGINAL SETTING	H	N ±1/32	X	AC
4-91025-41	25	1	1.28	.085	.035	1.31	2.75	1.31	2.72
4-91035-41	35	1	7.28	.085	.035	1.31	2.75	1.31	2.72
4-92050-41	50	2	7.91	.085	.035	1.31	3.25	1.81	3.34
4-92070-41	70	2	7.91	.085	.035	1.31	3.25	1.81	3.34
4-93075-41	75	3	8.53	.070	.040	1.31	3.75	2.31	3.97
4-93105-41	105	3	8.53	.070	.040	1.31	3.75	2.31	3.97
4-94125-41	125	4	9.16	.080	.050	1.43	4.25	2.81	4.60
4-95175-41	175	5	9.78	.080	.050	1.31	4.87	3.44	5.22

H = INSTALLED SPRING LENGTH  
D = MAGNET AIR GAP

THIS MATERIAL IS PROPERTY OF IDDS COMPANY. NO RIGHTS ARE GRANTED TO USE SUCH MATERIAL FOR ANY PURPOSE OTHER THAN (1) PRODUCT EVALUATION OR MAINTENANCE OR (2) THE PURSUIT OF SERVICES AND SUPPLIES TO THE IDDS COMPANY.

FILE: OUTLINE DWG. S9041 NEMA 4 END MOUNT (S8029 WITH ADAPTOR) WITH HUB SEAL

TOLERANCE UNLESS OTHERWISE NOTED:  
DIM ±.010 FRACTIONS ±.010  
HOLE ±.010

DATE: 06/07/08 SCALE: 1/2"=1"

ISSUED BY: 06/07/08

DESIGNED BY: 06/07/08

DRWING NO. L090153

1 of 1